# NSN 5320-01-343-8361

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-343-8361

Head	Ctvi	

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

### **Shank Diameter:**

Between 0.2641 inches and 0.2651 inches

### **Shank Style:**

Threaded self-plugging shank w/sleeve

### **Head Major Diameter:**

Between 0.3898 inches and 0.3948 inches

### **Expansion Device:**

Threaded sleeve

#### Lubrication:

Wax or cetyl alcohol or solid film

### **End Application:**

W/s: aircraft, hornet f/a-18

### **Grip Length:**

Between 0.595 inches and 0.656 inches

#### **Features Provided:**

Self-locking

### **Hardness Rating:**

39.0 rockwell c nut and 46.0 rockwell c nut

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

### Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

### **Material Specification:**

Qq-s-763 federal specification all material responses sleeve

### **Surface Treatment:**

Cadmium sleeve

### **Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

### Shelf Life:

N/a

### **Unit Of Measure:**

### **Demilitarization:**

No

# Fiig:

A040a0

## Mil-std (military Standard):

Mil-s-6758 spec.