# NSN 5320-01-344-1035

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-344-1035



# Thread Class:

3a

**Thread Direction:** 

Right-hand

# Fastener Length:

Between 1.135 inches and 1.155 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

Between 0.745 inches and 0.755 inches

# Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

220000 pounds per square inch

# Thread Size:

0.250 inches

# Shear Strength:

125000 single pounds per square inch

#### **Special Features:**

Light blue identification on top of head

# Material:

Nickel alloy 718

# Material Specification:

Ams 5662 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Spec. 258, cagec 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

# NSN 5320-01-344-1035

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

