NSN 5320-01-344-2516

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-344-2516

View Online at https://aerobasegroup.com/nsn/5320-01-344
Fastener Length:
Between 1.115 inches and 1.135 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.003 inches and 0.005 inches
Shank Diameter:
Between 0.155 inches and 0.158 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
Between 0.2396 inches and 0.2469 inches
Head Minor Diameter:
0.185 mils and 0.195 centimeters
Countersink Height:
0.0372 inches
Shear Strength:
37000 single pounds per square inch
Countersink Angle:
100.0 degrees
Heat Treatment:
T-4 solution heat treated
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Chromate
Surface Treatment Specification:
Mil-c-5541 military specification single treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard): Mil-c-5541 spec.

A040a0