# NSN 5320-01-344-4356

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-344-4356

Head Style

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

### **Shank Diameter:**

Between 0.2786 inches and 0.2796 inches

## **Shank Style:**

Threaded self-plugging shank w/sleeve

### **Head Major Diameter:**

Between 0.3898 inches and 0.3948 inches

#### **Expansion Device:**

Threaded sleeve

#### Lubrication:

Wax or cetyl alcohol or solid film

#### **Grip Length:**

Between 0.595 inches and 0.656 inches

#### **Features Provided:**

Self-locking

### **Hardness Rating:**

39.0 rockwell c nut and 46.0 rockwell c nut

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

#### **Material Specification:**

Qq-s-763 federal specification all material responses sleeve

#### **Surface Treatment:**

Cadmium sleeve

## **Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

#### Shelf Life:

N/a

## Unit Of Measure:

--

### Demilitarization:

No

# Fiig:

A040a0

## Mil-std (military Standard):

Mil-s-6758 spec.