NSN 5320-01-344-4363

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Fastener Length:

Between 1.065 inches and 1.085 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-344-4363

Head Style:					
Err-090					
Head Height:					
Between 0.045 inches and 0.055 inches					
Width Between Flats:					
Between 0.0791 inches and 0.0806 inches					
Shank Diameter:					
Between 0.1890 inches and 0.1895 inches					
Shank Style:					
Head Major Diameter:					
Between 0.295 inches and 0.315 inches					
Lubrication:					
Cetyl alcohol, specification 305, hi-shear corp					
Grip Length:					
Between 0.745 inches and 0.755 inches					
Thready Qty Per Inch (tpi):					
32					
Min. Tensile Strength (psi):					
220000 pounds per square inch					
Thread Size:					
0.190 inches					
Shear Strength:					
125000 single pounds per square inch					
Special Features:					
Light blue identification on top of head					
Material:					
Nickel alloy 718					
Material Specification:					
Ams 5662 assn standard single material response					
Surface Treatment:					
Passivate					
Surface Treatment Specification:					
Spec. 258, cagec 73197 mfr ref single treatment response					
Thread Series Designator:					
Unjf					

NSN 5320-01-344-4363

Pin-rivet - Page 2 of 2



She	lf	L	if	е	:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0