# NSN 5320-01-344-4365

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-344-4365



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.473 inches and 1.493 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.078 inches and 0.088 inches

# Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3740 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.565 inches and 0.600 inches

# Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

Between 0.933 inches and 0.943 inches

#### Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

220000 pounds per square inch

# Thread Size:

0.375 inches

# Shear Strength:

125000 single pounds per square inch

#### **Special Features:**

Light blue identification on top of head

#### Material:

Nickel alloy 718

#### **Material Specification:**

Ams 5662 assn standard single material response

#### Surface Treatment:

Passivate

# Surface Treatment Specification:

Spec. 258, cagec 73197 mfr ref single treatment response

#### **Thread Series Designator:**

Unjf

# NSN 5320-01-344-4365

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

