NSN 5320-01-344-5969

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Fastener Length:

Identification Code Color:

Between 1.722 inches and 1.742 inches

За

Red



View Online at https://aerobasegroup.com/nsn/5320-01-344-5969

Head Style:		
Err-090		
Head Height:		
Between 0.078 inches and 0.	.088 inches	
Width Between Flats:		
Between 0.1582 inches and	0.1617 inches	
Shank Diameter:		
Between 0.3735 inches and 0	0.3745 inches	
Shank Style:		
Pin-rivet, straight, threaded		
Head Major Diameter:		
Between 0.565 inches and 0.	.600 inches	
Lubrication:		
Cetyl alcohol, specification 3	05, hi-shear corp	
Grip Length:		
Between 1.182 inches and 1.	192 inches	
Thready Qty Per Inch (tpi):		
24		
Min. Tensile Strength (psi):		
210000 pounds per square in	nch	
Hardness Rating:		
45.0 rockwell c and 48.0 roc	ckwell c	
Thread Size:		
0.375 inches		
Shear Strength:		
125000 single pounds per sq	uare inch	
Special Features:		
Red identification color on top	o of head	
Material:		
Steel comp h11		
Material Specification:		
Ams 6487 assn standard sing	gle material response	
Surface Treatment:		
Cadmium and chromate		

NSN 5320-01-344-5969

Pin-rivet - Page 2 of 2



Surface Treatment Specification

Mil-c-8837, type 2, cl 2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-8837 spec.