## NSN 5320-01-344-5973

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

**Head Style:** 

**Thread Direction:** 

Fastener Length:

Between 1.315 inches and 1.335 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-344-5973

Err-090
Head Height:
Between 0.045 inches and 0.055 inches
Width Between Flats:
Between 0.0791 inches and 0.0801 inches
Shank Diameter:
Between 0.1890 inches and 0.1895 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.295 inches and 0.315 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.995 inches and 1.005 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.190 inches
Shear Strength:
125000 single pounds per square inch
Special Features:
Light blue identification on top of head
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Spec. 258, cagec 73197 mfr ref single treatment response
Thread Series Designator:
Unjf

## NSN 5320-01-344-5973

Pin-rivet - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0