NSN 5320-01-344-6768

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style: Err-090

Thread Direction:

Fastener Length:

Shank Diameter:

Between 1.474 inches and 1.499 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-344-6768

Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: 0.554 inches Tip Diameter: 0.3232 inches Lubrication: Cetyl alcohol and dry film End Application: Wsd: aircraft, eagle f-15 Grip Length: Between 0.990 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 9.9.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential Material:
Head Major Diameter: 0.554 inches Tip Diameter: 0.3232 inches Lubrication: Cetyl alcohol and dry film End Application: Wsd: aircraft, eagle f-15 Grip Length: Between 0.990 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
0.554 inches Tip Diameter: 0.3232 inches Lubrication: Cetyl alcohol and dry film End Application: Wsd: aircraft, eagle f-15 Grip Length: Between 0.990 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
Tip Diameter: 0.3232 inches Lubrication: Cetyl alcohol and dry film End Application: Wsd: aircraft, eagle f-15 Grip Length: Between 0.990 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
0.3232 inches Lubrication: Cetyl alcohol and dry film End Application: Wsd: aircraft, eagle f-15 Grip Length: Between 0.990 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 9.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
Lubrication: Cetyl alcohol and dry film End Application: Wsd: aircraft, eagle f-15 Grip Length: Between 0.990 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
Cetyl alcohol and dry film End Application: Wsd: aircraft, eagle f-15 Grip Length: Between 0.990 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
End Application: Wsd: aircraft, eagle f-15 Grip Length: Between 0.990 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
Wsd: aircraft, eagle f-15 Grip Length: Between 0.990 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
Grip Length: Between 0.990 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
Between 0.990 inches and 1.005 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
160000 pounds per square inch Thread Size: 0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
Thread Size: 0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
0.3125 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
Countersink Angle: Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
Between 99.0 degrees and 101.0 degrees Criticality Code Justification: Feat Special Features: Weapon system essential
Criticality Code Justification: Feat Special Features: Weapon system essential
Feat Special Features: Weapon system essential
Special Features: Weapon system essential
Weapon system essential
Material:
Iron alloy 660
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

NSN 5320-01-344-6768

Pin-rivet - Page 2 of 2



_						
C	he	14		iŧ	0	•
J			_		ㄷ	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0