## NSN 5320-01-347-0681

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-347-0681 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.583 inches and 1.608 inches **Head Style:** Err-090 **Head Height:** Between 0.082 inches and 0.094 inches **Shank Diameter:** 0.4194 inches **Head Major Diameter:** Between 0.605 inches and 0.619 inches **Tip Diameter:** 0.3967 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.177 inches and 1.192 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel comp 8740 or steel comp e4340 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5320-01-347-0681

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.