## NSN 5320-01-347-7239

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-347-7239

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.974 inches and 0.999 inches

## Head Style:

Err-090

#### Shank Diameter:

0.3403 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

0.647 inches

## Tip Diameter:

0.3336 inches

## Lubrication:

Dry film and cetyl alcohol

#### Grip Length:

Between 0.490 inches and 0.505 inches

## Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.375 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5737 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---



# NSN 5320-01-347-7239

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

