# NSN 5320-01-347-7260

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-347-7260



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 2.928 inches and 2.948 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.5951 inches and 0.6037 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

### **End Application:**

W/s: aircraft, b-2 bomber (atb)

### Grip Length:

Between 2.433 inches and 2.443 inches

#### Thready Qty Per Inch (tpi):

24

### Thread Size:

0.312 inches

### Shear Strength:

96000 single pounds per square inch

#### Countersink Angle:

130.0 degrees

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Thread Series Designator:

Unjf

# Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

No

# NSN 5320-01-347-7260

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

