## NSN 5320-01-347-8349

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-347-8349



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.785 inches and 1.805 inches

## Head Style:

Straight pan

## **Head Height:**

Between 0.130 inches and 0.140 inches

## Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3740 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.530 inches and 0.600 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## **End Application:**

W/s: helicopter, advance attack, ah-1w

## Grip Length:

1.250 inches

Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

160000 pounds per square inch

## **Thread Size:**

0.375 inches

## Material:

Titanium alloy uns r56400

## Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-347-8349

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

