# NSN 5320-01-347-8357

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-347-8357



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.427 inches and 0.447 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.037 inches and 0.047 inches

### Width Between Flats:

Between 0.0791 inches and 0.0801 inches

### Shank Diameter:

Between 0.1625 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.242 inches and 0.262 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.120 inches and 0.130 inches

### Thready Qty Per Inch (tpi):

32

## Thread Size:

0.164 inches

# Shear Strength:

95000 single pounds per square inch

## Material:

Titanium alloy uns r56400

# Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

# Surface Treatment:

Aluminum

# Surface Treatment Specification:

294, cagec 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjc

## Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5320-01-347-8357

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

