# NSN 5320-01-347-8366

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-347-8366



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.490 inches and 1.510 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.102 inches and 0.112 inches

# Width Between Flats:

Between 0.1270 inches and 0.1925 inches

#### Shank Diameter:

Between 0.3110 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.995 inches and 1.005 inches

#### Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.312 inches

# Shear Strength:

96000 single pounds per square inch

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

## Surface Treatment Specification:

Spec 294, cagec 73197 mfr ref single treatment response

# Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-347-8366

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

