NSN 5320-01-348-3662

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-348-3662 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.437 inches and 1.457 inches **Head Style:** Err-090 **Head Height:** Between 0.150 inches and 0.160 inches Width Between Flats: Between 0.1895 inches and 0.1930 inches **Shank Diameter:** Between 0.4365 inches and 0.4370 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.641 inches and 0.676 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.807 inches and 0.817 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.438 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-348-3662

Pin-rivet - Page 2 of 2



Fiig:

A528u0