

View Online at <https://aerobasegroup.com/nsn/5320-01-349-0962>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.614 inches and 0.634 inches

Head Style:

Err-090

Head Height:

Between 0.037 inches and 0.047 inches

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Shank Diameter:

Between 0.1630 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.242 inches and 0.262 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.307 inches and 0.317 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

210000 pounds per square inch

Thread Size:

0.164 inches

Shear Strength:

125000 single pounds per square inch

Special Features:

Light blue identification on top of head

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258, cagc 73197 mfr ref single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0