

View Online at <https://aerobasegroup.com/nsn/5320-01-349-0965>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.500 inches and 1.520 inches

Head Style:

Err-090

Head Height:

Between 0.093 inches and 0.105 inches

Width Between Flats:

Between 0.1895 inches and 0.1930 inches

Shank Diameter:

Between 0.4365 inches and 0.4370 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.641 inches and 0.676 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.870 inches and 0.880 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Thread Size:

0.438 inches

Shear Strength:

125000 single pounds per square inch

Special Features:

Light blue identification on top of head

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258, caged 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0