## NSN 5320-01-349-0966

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

**Head Style:** 

**Thread Direction:** 

Fastener Length:

Between 0.697 inches and 0.717 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-349-0966

Err-090		
Head Height:		
Between 0.059 inches and 0.069 inches		
Width Between Flats:		
Between 0.0947 inches and 0.0967 inches		
Shank Diameter:		
Between 0.2490 inches and 0.2495 inches		
Shank Style:		
Pin-rivet, straight, threaded		
Head Major Diameter:		
Between 0.387 inches and 0.412 inches		
Lubrication:		
Cetyl alcohol, specification 305, hi-shear corp		
Grip Length:		
Between 0.307 inches and 0.317 inches		
Thready Qty Per Inch (tpi):		
28		
Min. Tensile Strength (psi):		
210000 pounds per square inch		
Thread Size:		
0.250 inches		
Shear Strength:		
125000 single pounds per square inch		
Special Features:		
Light blue identification on top of head		
Material:		
Nickel alloy 718		
Material Specification:		
Ams 5662 assn standard single material response		
Surface Treatment:		
Passivate		
Surface Treatment Specification:		
258, cagec 73197 mfr ref single treatment response		
Thread Series Designator:		
Unjf		

## NSN 5320-01-349-0966

Pin-rivet - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0