## NSN 5320-01-349-1862

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-349-1862 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.224 inches and 1.249 inches **Head Style:** Err-090 **Shank Diameter:** 0.3690 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.681 inches Tip Diameter: 0.3571 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.740 inches and 0.755 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5320-01-349-1862

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0