## NSN 5320-01-349-9762

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/r	nsn/5320-01-349-9762
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Fastener Length:	
Between 1.003 inches and 1.023 inches	
Head Style:	
Err-090	
Head Height:	
Between 0.064 inches and 0.074 inches	
Width Between Flats:	
Between 0.0791 inches and 0.0806 inches	
Shank Diameter:	
Between 0.1890 inches and 0.1895 inches	
Shank Style:	
Head Major Diameter:	
Between 0.357 inches and 0.377 inches	
Lubrication:	
Cetyl alcohol, specification 305, hi-shear c	corp
End Application:	
W/s: aircraft, prowler ea-6b	
Grip Length:	
Between 0.683 inches and 0.693 inches	
Thready Qty Per Inch (tpi):	
32	
Min. Tensile Strength (psi):	
210000 pounds per square inch	
Thread Size:	
0.190 inches	
Shear Strength:	
125000 single pounds per square inch	
Special Features:	
Light blue identification on top of head	
Material:	
Nickel alloy 718	
Material Specification:	

Ams 5662 assn standard single material response

**Surface Treatment:** 

Passivate

**Surface Treatment Specification:** 

258, cagec 73197 mfr ref single treatment response

## NSN 5320-01-349-9762

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A528u0