

View Online at <https://aerobasegroup.com/nsn/5320-01-349-9770>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.003 inches and 2.023 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.683 inches and 1.693 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

220000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

125000 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Light blue identification on top of head

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Spec. 258, cagec 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0