NSN 5320-01-349-9773

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-349-9773



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.003 inches and 2.023 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

W/s: aircraft, tomcat f-14

Grip Length:

Between 1.683 inches and 1.693 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5320-01-349-9773

Pin-rivet - Page 2 of 2

Fiig: A528u0

