# NSN 5320-01-350-7127

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-350-7127

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.1625 inches and 0.1645 inches

# Shank Style:

Threaded self-plugging shank w/sleeve

# Head Major Diameter:

Between 0.325 inches and 0.335 inches

## **Expansion Device:**

Threaded stem

Lubrication:

Dry film or cetyl alcohol or paraffin wax

## Grip Length:

Between 0.150 inches and 0.200 inches

#### **Countersink Angle:**

Between 129.0 degrees and 131.0 degrees

## **Special Features:**

Complete top surface of nut head shall be powder blasted to produce a surface finish of ra 50/80 micro inches after all manufacturing

operations. Powder blasting on remainder of nut body is optional

## Material:

Titanium alloy uns r56400 nut

## **Material Specification:**

Mil-t-9047 military specification 1st material response nut or ams 4928 assn standard 2nd material response nut or ams 4967 assn standard

3rd material response nut

Surface Treatment:

Passivate stem

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response stem

Shelf Life:

N/a

## Unit Of Measure:

```
--
```

```
Demilitarization:
```

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-t-9047 spec.