NSN 5320-01-351-2336

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-351-2336 Fastener Length: 0.326 inches **Head Style: Brazier Head Height:** Between 0.080 inches and 0.090 inches **Shank Diameter:** Between 0.200 inches and 0.204 inches **Shank Style:** Straight **Head Major Diameter:** Between 0.356 inches and 0.394 inches **Expansion Device:** Break stem **Grip Length:** Between 0.205 inches and 0.209 inches Min. Tensile Strength (psi): 490 pounds per square inch **Shear Strength:** 855 single pounds per square inch Material: Aluminum alloy 2024 expanderaluminum alloy 5056 locking ringaluminum alloy 5056 sleeve **Material Specification:** Qq-a-430 federal specification single material response expanderqq-a-430 federal specification single material response locking ringqq-a-430 federal specification single material response sleeve **Surface Treatment:** Anodize expander **Surface Treatment Specification:** Mil-a-8625 military specification 1st treatment response expander or mil-c-5541 military specification 2nd treatment response expander Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig: A040a0

Mil-std (military Standard):

Mil-a-8625 spec.

No