

View Online at <https://aerobasegroup.com/nsn/5320-01-351-2336>

**Fastener Length:**

0.326 inches

**Head Style:**

Brazier

**Head Height:**

Between 0.080 inches and 0.090 inches

**Shank Diameter:**

Between 0.200 inches and 0.204 inches

**Shank Style:**

Straight

**Head Major Diameter:**

Between 0.356 inches and 0.394 inches

**Expansion Device:**

Break stem

**Grip Length:**

Between 0.205 inches and 0.209 inches

**Min. Tensile Strength (psi):**

490 pounds per square inch

**Shear Strength:**

855 single pounds per square inch

**Material:**

Aluminum alloy 2024 expanderaluminum alloy 5056 locking ringaluminum alloy 5056 sleeve

**Material Specification:**

Qq-a-430 federal specification single material response expanderqq-a-430 federal specification single material response locking ringqq-a-430 federal specification single material response sleeve

**Surface Treatment:**

Anodize expander

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response expander or mil-c-5541 military specification 2nd treatment response expander

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.