

View Online at <https://aerobasegroup.com/nsn/5320-01-351-2918>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.690 inches and 0.710 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.2966 inches and 0.3016 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.370 inches and 0.380 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Shear Strength:**

95000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Spec. 294, cagec 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0