

View Online at <https://aerobasegroup.com/nsn/5320-01-351-4358>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.8805 inches and 2.9055 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.240 inches and 0.252 inches

**Shank Diameter:**

Between 0.5890 inches and 0.5895 inches

**Shank Style:**

Blind rivet, nut and bolt assembly

**Head Major Diameter:**

Between 0.877 inches and 0.893 inches

**Lubrication:**

Dry film and cetyl alcohol

**End Application:**

C-17

**Grip Length:**

Between 2.1825 inches and 2.1975 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

27500 pounds per square inch

**Thread Size:**

0.500 inches

**Shear Strength:**

37300 double pounds per square inch

**Product Name:**

Pin-riquet, threaded

**Special Features:**

W/sleeve

**Material:**

Titanium alloy uns r56400 bolt

**Material Specification:**

Astm-a269 assn standard single material response sleeve or mil-t-8504 military specification single material response sleeve

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-t-8504 spec.