

View Online at <https://aerobasegroup.com/nsn/5320-01-351-4360>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.2695 inches and 2.2945 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.4470 inches and 0.4475 inches

Shank Style:

Blind rivet, nut and bolt (assembly)

Head Major Diameter:

Between 0.7650 inches and 0.8380 inches

Expansion Device:

Threaded stem

Lubrication:

Solid film and cetyl alcohol

Grip Length:

Between 1.6775 inches and 1.6925 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

15200 pounds per square inch

Thread Size:

0.3750 inches

Shear Strength:

21000 double pounds per square inch

Countersink Angle:

Between 102.0 degrees and 103.0 degrees

Material:

Titanium alloy uns r56400 bolt

Material Specification:

II-t-8504 military specification 10th material response sleeve

Surface Treatment:

Passivate bolt

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response bolt

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

spec.