

View Online at <https://aerobasegroup.com/nsn/5320-01-351-4367>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.5625 inches and 1.5825 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.1895 inches and 0.1930 inches

**Shank Diameter:**

Between 0.4360 inches and 0.4370 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.8812 inches and 0.8884 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.9325 inches and 0.9425 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

210000 pounds per square inch

**Thread Size:**

0.438 inches

**Shear Strength:**

125000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

258, cagec 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0