NSN 5320-01-351-5635

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-351-5635



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.1900 inches and 1.2100 inches

Head Style:

Err-090

Head Height:

Between 0.0640 inches and 0.0740 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.3570 inches and 0.3770 inches

End Application:

W/s: aircraft, starlifter c-141; aircraft, hornet f/a-18

Grip Length:

Between 0.8700 inches and 0.8800 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

4350 pounds per square inch

Thread Size:

0.1900 inches

Collar Style:

Straight type

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-01-351-5635

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

