# NSN 5320-01-351-5639

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-351-5639



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.9400 inches and 0.9600 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

### Grip Length:

Between 0.6200 inches and 0.6300 inches

#### Thready Qty Per Inch (tpi):

32

### Thread Size:

0.190 inches

### Shear Strength:

125000 single pounds per square inch

#### Material:

Nickel alloy 718

#### **Material Specification:**

Ams 5662 assn standard single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-351-5639

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

