

View Online at <https://aerobasegroup.com/nsn/5320-01-351-6333>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.753 inches and 0.773 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.433 inches and 0.443 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

210000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

125000 single pounds per square inch

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Spec 258, cagec 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0