
## NSN 5320-01-351-6334

Pin-rivet - Page 1 of 2



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 2.760 inches and 2.780 inches

#### Head Style:

Err-090

## Head Height:

Between 0.200 inches and 0.210 inches

#### Width Between Flats:

Between 0.2520 inches and 0.2556 inches

#### Shank Diameter:

Between 0.5610 inches and 0.5615 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.842 inches and 0.877 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

Between 1.995 inches and 2.005 inches

#### Thready Qty Per Inch (tpi):

18

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Thread Size:

0.562 inches

#### Shear Strength:

95000 single pounds per square inch

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Thread Series Designator:

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No



# NSN 5320-01-351-6334

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

