

View Online at <https://aerobasegroup.com/nsn/5320-01-351-6400>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.6145 inches and 1.6395 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.175 inches and 0.187 inches

**Shank Diameter:**

Between 0.4310 inches and 0.4315 inches

**Shank Style:**

Blind rivet, nut and bolt assembly

**Head Major Diameter:**

Between 0.704 inches and 0.718 inches

**Lubrication:**

Dry film and cetyl alcohol

**End Application:**

C-17

**Grip Length:**

Between 1.0575 inches and 1.0725 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

15200 pounds per square inch

**Hardness Rating:**

45.0 rockwell c bolt

**Thread Size:**

0.3750 inches

**Shear Strength:**

21000 double pounds per square inch

**Product Name:**

Pin-riquet, threaded

**Special Features:**

Sleeve included

**Material:**

Titanium alloy uns r56400 bolt

**Material Specification:**

Astm-a269 assn standard single material response sleeve or mil-t-8504 military specification single material response sleeve

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-t-8504 spec.