

View Online at <https://aerobasegroup.com/nsn/5320-01-351-6400>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.6145 inches and 1.6395 inches

Head Style:

Err-090

Head Height:

Between 0.175 inches and 0.187 inches

Shank Diameter:

Between 0.4310 inches and 0.4315 inches

Shank Style:

Blind rivet, nut and bolt assembly

Head Major Diameter:

Between 0.704 inches and 0.718 inches

Lubrication:

Dry film and cetyl alcohol

End Application:

C-17

Grip Length:

Between 1.0575 inches and 1.0725 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

15200 pounds per square inch

Hardness Rating:

45.0 rockwell c bolt

Thread Size:

0.3750 inches

Shear Strength:

21000 double pounds per square inch

Product Name:

Pin-riquet, threaded

Special Features:

Sleeve included

Material:

Titanium alloy uns r56400 bolt

Material Specification:

Astm-a269 assn standard single material response sleeve or mil-t-8504 military specification single material response sleeve

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-t-8504 spec.