

View Online at <https://aerobasegroup.com/nsn/5320-01-351-6404>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.8945 inches and 1.9195 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.4470 inches and 0.4475 inches

**Head Major Diameter:**

Between 0.7500 inches and 0.8230 inches

**Expansion Device:**

Threaded stem

**Lubrication:**

Solid film and cetyl alcohol

**Grip Length:**

Between 1.3025 inches and 1.3175 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

15200 pounds per square inch

**Thread Size:**

0.3750 inches

**Shear Strength:**

21000 double pounds per square inch

**Countersink Angle:**

Between 102.0 degrees and 103.0 degrees

**Material:**

Titanium alloy uns r56400 bolt

**Material Specification:**

II-t-8504 military specification 10th material response sleeve

**Surface Treatment:**

Passivate bolt

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response bolt

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

spec.