# NSN 5320-01-351-6408

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-351-6408



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.177 inches and 1.197 inches

### Head Style:

Err-090

#### **Head Height:**

Between 0.037 inches and 0.047 inches

## Width Between Flats:

Between 0.0791 inches and 0.0801 inches

### Shank Diameter:

Between 0.1625 inches and 0.1635 inches

### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.242 inches and 0.262 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.870 inches and 0.880 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.164 inches

## Shear Strength:

95000 single pounds per square inch

# **Special Features:**

Hi-kote 1 aluminum coating per hi-shear spec. 294.

## Material:

Titanium alloy uns r56400

# Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-351-6408

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

