## NSN 5320-01-351-6410

Pin-rivet - Page 1 of 2

**Unit Of Measure:** 



View Online at https://aerobasegroup.com/nsn/5320-01-351-6410 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.003 inches and 2.023 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.683 inches and 1.693 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp 431 **Material Specification:** Ams 5628 federal specification 1st material response or mil-s-18732 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

## NSN 5320-01-351-6410

Pin-rivet - Page 2 of 2



D	:1:4.	-:-	-4:-	
Dem	HIT	arız	atıc	on:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.