NSN 5320-01-351-6412

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-351-6412 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.425 inches and 1.445 inches **Head Style:** Err-090 **Head Height:** Between 0.178 inches and 0.188 inches Width Between Flats: Between 0.2520 inches and 0.2555 inches **Shank Diameter:** Between 0.4990 inches and 0.4995 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.735 inches and 0.770 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.745 inches and 0.755 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.500 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-351-6412

Pin-rivet - Page 2 of 2



Fiig:

A528u0