# NSN 5320-01-351-6416

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-351-6416



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.815 inches and 1.835 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

## Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.295 inches and 0.315 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## **End Application:**

W/s: aircraft, tomcat f-14

Grip Length:

Between 1.495 inches and 1.505 inches

## Thready Qty Per Inch (tpi):

32

# Thread Size:

0.190 inches

# Shear Strength:

95000 single pounds per square inch

## **Collar Style:**

Straight type

#### Material:

Titanium alloy uns r56400

## Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-351-6416

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

