# NSN 5320-01-351-8813

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-351-8813



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.2520 inches and 1.2720 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.0640 inches and 0.0740 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3570 inches and 0.3770 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.9320 inches and 0.9420 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.1900 inches

## Shear Strength:

95000 single pounds per square inch

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Thread Series Designator:

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-351-8813

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

