## NSN 5320-01-351-8815

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-351-8815



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 3.0525 inches and 3.0725 inches

#### Head Style:

Cooper's

#### **Head Height:**

Between 0.0800 inches and 0.0840 inches

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.8670 inches and 0.9010 inches

#### Lubrication:

Cetyl alcohol

#### Grip Length:

Between 2.5575 inches and 2.5675 inches

#### Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

95000 pounds per square inch

#### **Thread Size:**

0.3125 inches

#### **Countersink Angle:**

Between 155.0 degrees and 157.0 degrees

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Thread Series Designator:

Unjf

### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-351-8815

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

