

View Online at <https://aerobasegroup.com/nsn/5320-01-351-9336>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2580 inches and 0.2600 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

0.463 inches

Expansion Device:

Threaded stem

Lubrication:

Dry film or cetyl alcohol or paraffin wax or carbo wax

Grip Length:

0.594 inches

Features Provided:

Drive nut

Min. Tensile Strength (psi):

160000 pounds per square inch

Shear Strength:

75000 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Drive nut mild steel, color light gray with corrosion resistant coating

Material:

Titanium alloy uns r56400 bolttitanium alloy uns r56400 nutsteel comp 303se sleeve or steel comp 303 sleeve or steel comp 304 sleeve

Material Specification:

Ams 4928 assn standard single material response bolt or ams 4967 assn standard single material response boltams 4928 assn standard single material response nut or ams 4967 assn standard single material response nutams 5641 assn standard 1st material response sleeve or astm a582 assn standard 2nd material response sleeve or ams 5639 assn standard 3rd material response sleeve

Surface Treatment:

Passivate sleeve

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0