

View Online at <https://aerobasegroup.com/nsn/5320-01-351-9337>

**Head Style:**

Hexagon

**Head Height:**

0.160 inches

**Shank Diameter:**

Between 0.3095 inches and 0.3115 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Threaded stem

**Lubrication:**

Cetyl alcohol or paraffin wax or carbo wax or dry film

**Grip Length:**

0.531 inches

**Width Across Flats:**

0.479 inches

**Features Provided:**

Drive nut

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Shear Strength:**

75000 single pounds per square inch

**Special Features:**

Drive nut mild steel, color light gray with corrosion resistant coating

**Material:**

Titanium alloy uns r56400 bolttitanium alloy uns r56400 nutsteel comp 303se sleeve or steel comp 303 sleeve or steel comp 304 sleeve

**Material Specification:**

Ams 4928 assn standard single material response bolt or ams 4967 assn standard single material response boltams 4928 assn standard single material response nut or ams 4967 assn standard single material response nutams 5641 assn standard 1st material response sleeve or astm a582 assn standard 2nd material response sleeve or ams 5639 assn standard 3rd material response sleeve

**Surface Treatment:**

Passivate sleeve

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0