## NSN 5320-01-351-9338

Blind Rivet - Page 1 of 1



view Online at https://aerobasegroup.com/nsn/5520-01-551-9556
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.2580 inches and 0.2600 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
0.463 inches
Expansion Device:
Threaded stem
Lubrication:
Dry film or paraffin wax or cetyl alcohol
Grip Length:
Between 0.407 inches and 0.469 inches
Features Provided:
Drive nut
Hardness Rating:
30.0 rockwell c bolt and 45.0 rockwell c bolt30.0 rockwell c nut and 45.0 rockwell c nut
Countersink Angle:
Between 99.0 degrees and 101.1 degrees
Special Features:
Drive nut mild steel, color black with corrosion resistant coating, top surface of head of nut powder blasted
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:

A040a0