# NSN 5320-01-351-9339

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-351-9339

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.2580 inches and 0.2600 inches

# Shank Style:

Threaded self-plugging shank w/sleeve

# Head Major Diameter:

0.463 inches

#### **Expansion Device:**

Threaded stem

#### Lubrication:

Dry film or paraffin wax or cetyl alcohol

#### Grip Length:

Between 0.532 inches and 0.594 inches

#### **Features Provided:**

Drive nut

Hardness Rating:

30.0 rockwell c bolt and 45.0 rockwell c bolt30.0 rockwell c nut and 45.0 rockwell c nut

#### **Countersink Angle:**

Between 99.0 degrees and 101.1 degrees

## **Special Features:**

Drive nut mild steel, color black with corrosion resistant coating, top surface of head of nut powder blasted

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

#### Surface Treatment:

Passivate

#### **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

Shelf Life:

N/a

```
Unit Of Measure:
```

---

```
Demilitarization:
```

No

Fiig:

A040a0