
## NSN 5320-01-351-9388

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.1750 inches and 1.1950 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2797 inches and 0.2807 inches

Shank Style:

#### Head Major Diameter:

Between 0.5018 inches and 0.5066 inches

Lubrication:

Cetyl alcohol

#### Grip Length:

Between 0.7450 inches and 0.7550 inches

## Thready Qty Per Inch (tpi):

28

#### **Thread Size:**

0.250 inches

#### Shear Strength:

125000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

Estricted usage for repair work only

#### Material:

Nickel alloy 718

#### **Material Specification:**

Ams 5662 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-351-9388

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

