## NSN 5320-01-351-9388

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-351-9388 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.1750 inches and 1.1950 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2797 inches and 0.2807 inches **Shank Style: Head Major Diameter:** Between 0.5018 inches and 0.5066 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.7450 inches and 0.7550 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Estricted usage for repair work only Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-01-351-9388

Pin-rivet - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A528u0