
# NSN 5320-01-351-9445

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 2.9275 inches and 2.9475 inches

#### Head Style:

Cooper's

#### **Head Height:**

Between 0.0800 inches and 0.0840 inches

#### Width Between Flats:

Between 0.1270 inches and 0.1296 inches

#### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.8670 inches and 0.9010 inches

# Lubrication:

Cetyl alcohol

# Grip Length:

Between 2.4325 inches and 2.4425 inches

### Thready Qty Per Inch (tpi):

24

### Min. Tensile Strength (psi):

95000 pounds per square inch

### **Thread Size:**

0.3125 inches

### **Countersink Angle:**

Between 155.0 degrees and 157.0 degrees

#### Material:

Titanium alloy uns r56400

### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

### Thread Series Designator:

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-351-9445

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

